



Chroma-Q®
BRILLIANT SOLUTIONS

Chroma-Q The Force™

“Chroma-Q The Force”, is a versatile multi-tool designed for the dedicated lighting professional. This robust device streamlines the firmware update process across a wide range of Chroma-Q products, including the 2inspire series.



With the capacity to store numerous firmware versions for various products, “Chroma-Q The Force”, ensures that your equipment is always up-to-date, whether through RS485 or Ethernet connections.

Additionally, its RDM management capabilities allow for remote addressing and configuration of RDM-compatible devices, while the integrated DMX viewer provides real-time monitoring of DMX signals, making it an indispensable tool for service centers, rental shops, and road crews alike.

The Technician’s Essential Companion

Chroma-Q The Force™

Features

- Multi-Product Firmware Storage: “Chroma-Q The Force”, can hold various firmware revisions for a multitude of Chroma-Q products simultaneously.
- Dual Update Compatibility: Offers both RS485 and Ethernet firmware updates, providing flexibility in connectivity and use.
- RDM Management: Equipped with RDM manage tools for remote addressing and adjustments on RDM compatible devices.
- DMX Signal Monitoring: Features a DMX viewer to observe and diagnose DMX signal integrity in real-time.
- User-Friendly Interface: Designed with a straightforward interface for easy navigation and operation by professionals.
- Portable Design: Crafted for convenience, its compact and durable design makes it ideal for on-the-go technicians and roadies.



ORDERING INFORMATION

CQ1527-1000: Chroma-Q The Force multi-purpose tool

SPECIFICATIONS

Net dimensions:	Width: 180mm / 7.1" Height: 84mm / 3.3" Depth: 136mm / 5.35"
Net weight:	1.2kg / 2.5lbs
Shipping dimensions:	Width: 256mm / 10" Height: 130mm / 5.12" Depth: 220mm / 8.66"
Shipping weight:	1.79kg / 3.95lbs
Colour:	Dark Grey
IP Rating	IP20
Cooling System	Convection
Operating Temperature	0°C to 40°C

Construction	Powder-coated steel
Control Protocol	Artnet, sACN, DMX
Power Input:	DC USB-C PD or PoE AF
Power Input Rating	9-12VDC for USB C input / 44-57 VDC for PoE input
Power Consumption	5W
Rated input current	0.6A
Idle Power Consumption	5W
Power connector:	USB-C / RJ45
Ethernet connector In:	RJ45
DMX connector Out:	XLR5 F
DMX connector In:	XLR5 M
Data to PC	USB Type B
Data to External drive	USB Type A
SB-C PD supply	Included
USB-C PD Cable	Included

To arrange your personal demonstration or for more information, contact us at:
sales@chroma-q.com
 or visit **www.chroma-q.com/theforce**



Chroma-Q®
BRILLIANT SOLUTIONS



A.C. Entertainment Technologies

UK & International Sales
Tel: +44 (0)1494 446000
sales@ac-et.com
www.ac-et.com

Northern UK Sales
Tel: +44 (0)113 255 7666
acnorth@ac-et.com
www.ac-et.com

AC-ET Ireland
Tel: +353 87 4600 202
sales@ac-et.ie
www.ac-et.ie



North American Sales
A.C. Lighting
Tel: +1 416-255-9494
northamerica@aclighting.com
www.aclighting.com

Japanese Sales
A.C. Lighting Asia KK
Tel: +81 (0)3-6907-1758
sales@aclighting.jp
www.aclighting.jp

Chroma-Q and all associated product names are recognised trademarks, for more information visit www.chroma-q.com/trademarks. The rights and ownership of all trademarks are recognised. Whilst every effort has been made to ensure that the information is correct, Chroma-Q accepts no liability for errors or omissions. Technical specifications and data are provided for guidance only. Because we constantly aim to improve our products, we reserve the right to amend or alter at any time and without prior notice, the specifications of any product. Consult the website for current models and specifications. E&OE.