

Specification Sheet - Version: 1.1 Chroma-Q™ Studio Force V Compact™ Powerful Variable White LED Workhorse Fixture Part No: CHSFCV

DESCRIPTION

The fixture shall provide 3,000K - 6,100K CCT variable white light output. The fixture shall feature a compact design.

The fixture shall provide a very powerful 2,600 hot lumens output for washing large areas.

The fixture shall be IP65 rated.

The fixture shall be suitable for a wide range of entertainment lighting disciplines, including uplighting, pipe-end, shin busting, backlighting, truss toner and other wash applications.

The fixture shall be suitable for floor, wall or truss mounting. The fixture shall provide a smooth, linear dimming curve.

The fixture shall feature an external power supply - Force Compact PSU15. The fixture shall allow daisy-chaining of up to five units on a single PSU15 output.

The fixture shall be compatible with selected City Theatrical accessories. The fixture shall provide a CRI of 80.

The fixture shall feature a built-in stand-alone mode with real-time triggering.

The fixture shall be manufactured from extruded material.

FEATURES

- 3.000K 6.100K CCT variable white
- Laboratory calibrated 3200°K and 5600°K presets
- Compact yet powerful 2,600 lumens from a very small footprint
- IP65 rated*
- Multi-purpose workhorse fixture suitable for a wide range of applications
- Extremely smooth, uniform wash
- Theatrical grade dimming
- · Ideal for TV, film, touring, exhibitions, corporate events and theatre
- Camera-friendly
- Custom optics ensure a smooth even beam
- Accepts City Theatrical accessories use with your existing accessories inventory

ORDERING INFORMATION

CHSFCV: Chroma-Q Studio Force V Compact LED Fixture CHCFCPSU15: Chroma-Q Force Compact 15-Way Power Supply (to suit up to 15 fixtures)

ACCESSORIES

CHCFCTH: ***Top Hat For Compact - Black CHCFCHTH: ***Half Top Hat For Compact - Black CHCFCECL: ***Egg Crate Louver For Compact - Black CHCFCBD: ***Barn Door For Compact - Black

CHCFCCL: Clear Glass For Compact (Comes with fixture)
CHCFCFL: Frosted Glass For Compact (Comes with fixture)
CHCFCAH: Color Force Accessory Holder (Comes with fixture)
CHCFCDMXOP: W-DMX Wireless Option For PSU-15

***City Theatrical accessories.

OVERALL SPECIFICATIONS

Net weight:

Shipping dimensions:

Net dimensions (without fixings): Width: 212mm / 8.4"

Height: 196mm / 7.7" Depth: 152mm / 6" 4 kgs / 8.5 lbs Width: 267mm / 10.5"

Height: 254mm / 10" Depth: 241mm / 9.5"

Shipping Weight: 5.4kgs / 12 lbs

Power & Connections: Daisy-chained power & data connections

Power Supply: External - PSU15
Power Input Rating: 48V DC

Power Input Rating: 48V D Power Consumption: 60W

Typical Power & Current: Measurements done with all LEDs at max.

intensity. Measurements made at nominal voltage. Allow for deviation of +/- 10%

Power Connector In/Out: XLR 4-pin
Data Connectors In/Out: XLR 4-pin

Max Cable Run: ~60m / 200ft (PSU to last unit)
Control Protocol: ANSI E1.11 USITT DMX 512-A

Cooling System: Convection
Operating Temperature: 0°C to 40°C

Construction: Cast machined aluminium

Colour: Black

Built-In Hardware: Yoke assembly IP Rating: *IP65

Approvals: CISPR 22:2006/EN55022:2006 & CISPR

24:1997/EN55024:1998, ICES-003:2004,

FCC Part 15 Subpart B:2010

LED Engines:

LEDs Per Engine: 14 Cold White / 14 Warm White

Total LEDs: 28

Control Modes (PSU15): 30 channels WW/CW, 30 channels CTI,

2 channels WW/CW, 2 channels CTI, 1 channel Look Select, Master Standalone,

Slave Standalone

Dimming Curve: Theatrical Variable Effects Engine: Yes

Effects Parameters: Intensity effects

Hot Lumen Output (Combined): 2,630 hot lumens @ 4,300K Optics: Specialised close focus lens

Beam Angle: 14° (approx.)


Beam Angle With


(Optional Frosted Optic): 21° (approx.)


Beam Distribution: Asymmetrical direct illumination CCT: 3,000K - 6,000K (+/- 200K)
Colour Gamut: Performance enhanced
CRI: ~80 @ 4,300K
Lamp Life: L70 at 50,000 hours




Specification Sheet - Version: 1.1 Chroma-Q™ Studio Force V Compact™ Powerful Variable White LED Workhorse Fixture Part No: CHSFCV







Force Compact 15-Way Power Supply





Chroma-Q and all associated product names are recognised trademarks, for more information visit www.chroma-q.com/trademarks. The rights and ownership of all trademarks are recognised. The information contained herein is correct at the time of printing, however as we are constantly refining our product range we reserve the right to change the specification without notice. E&DE.