



# Extreme Output Daylight White LED Battens

......

Utilising the same core technologies as the innovative Chroma-Q<sup>TM</sup> Color Force<sup>TM</sup> LED battens range, the new Studio Force<sup>TM</sup> V 48 & 72 models are 3,000K - 6,100K CCT variable white versions featuring laboratory calibrated 3200oK and 5600oK presets that are specifically designed for TV, film, touring, exhibitions, corporate events and theatre lighting applications. With an extreme output of up to 25,400 lumens, the battens evenly wash large areas, complemented by smooth, theatrical grade dimming. The range also includes a multi-purpose version.

### **Extreme Output**

Available in a choice of 1.2m / 4ft (48) and 1.8m / 6ft (72) batten lengths, the fixtures offer more than twice the white light output of their RGBA colour variants - ranging from 16,900 lumens (48) up to 25,400 lumens (72).

### Multi-purpose

The Studio Force V battens are suitable for a wide range of lighting applications, including key-lighting, uplighting, backlighting and wash applications.

Optional accessories include a cyc lens and a border light lens for general purpose wash applications, and a half snoot.

### Colour

The Studio Force V range includes ColorSure™ technology for enhanced consistency across each light engine and when using multiple fixtures.

### **Optics & Dimming**

The Studio Force V range's camera friendly custom optical design provides a smooth, uniform output, matched by theatrical grade dimming.



PowerCon and 5-pin DMX connections in at one end and out the other

# **Practical & Mechanical**

On the outside, the Studio Force V battens have been designed to provide maximum versatility and ease of use. The built-in power supply, hidden quick release fixings requiring no tools, and PowerCon and 5-pin DMX connections in at one end and out the other provide fast deployment and simple cable management.

The Studio Force V range also features stand-alone Master and Slave modes for additional usage possibilities, flat end plates for seamless wall-washing and a rugged extruded aluminium body.



Hidden quick release fixings and flat end plates

Half snoot

# Key Features

- 3.000K 6.100K CCT variable white
- Extreme output 16,900 lumens (48) / 25,400 lumens (72)
- Extremely smooth, uniform wash
- Theatrical grade dimming
- Ideal for TV, film, touring, exhibitions, corporate events and theatre
- Choice of 1.2m / 4ft (48) and 1.8m / 6ft (72) lengths
- Camera friendly
- Laboratory calibrated 3,200oK and 5,600oK presets
- PowerCon input and output for easy daisy chaining of fixtures
- Optional cyc and border light lens media accessories
- Flat end plates for seamless wall-washing
- Built-in power supply
- Hidden quick release fixings
- Rugged extruded aluminium body



# Studio Force V 48 & 72 Technical Specification

	Studio Force V 48	Studio Force V 72
Product Code	CHSFV48NF	CHSFV72NF
Net Dimensions**	1,181mm x 182mm x 177mm / 46.5" x 7.25" x 7"	1,759mm x 182mm x 177mm / 69.25" x 7.25" x 7"
Net Weight	15kgs / 33lbs	22kgs / 48lbs
Shipping Dimensions	1,295mm x 305mm x 320mm / 51" x 12" x 12.5"	1,855mm x 305mm x 320mm / 73" x 12" x 12.5"
Shipping Weight	18kgs / 40lbs	25kgs / 56lbs
Power Input Rating	100-240V AC, 50-60 Hz, 400VA	100-240V AC, 50-60 Hz, 700VA
Typical Power & Current	Measurements done with all LEDs at max. intensity. Measurements made at nominal voltage. Allow for a deviation of $\pm$ 10%.	

	Studio Force V 48 & 72
Power Connector In/Out	PowerCon
Data Connectors In/Out	XLR 5-pin
Control Protocol	ANSI E1.11 USITT DMX 512-A
Cooling System	Forced - 2 fans
Construction	Anodised aluminium extrusion
Colour	Black
Built-In Hardware	Quick release lever for tilt adjustment
IP Rating	IP20
Approvals	CISPR 22 :2006/EN55022 :2006 & CISPR 24 :1997/EN55024 :1998, ICES-003 :2004 & FCC Part 15 Subpart B: 2007, Typical Power CSA C22. No. 166-M1983:R2008 UL 1573:2003; UL 8750

<sup>\*\*</sup>For exact measurements please refer to the line drawings found in the product specification sheets and manuals on www.chroma-q.com

# **Control** & Photometric

	Studio Force V 48	Studio Force V 72
LED Engines	8	12
LEDs Per Engine	12 Cold White / 12 Warm White	
Total LEDs	192	288
Control Modes	32 channels Dim32 3 channels FxCTI 2 channels WW/CW 2 channels CTI 1 channel Look Select Master Standalone Slave Standalone Manual	48 channels Dim48 3 channels FxCTI 2 channels WW/CW 2 channels CTI 1 channel Look Select Master Standalone Slave Standalone Manual
Dimming Curve	Theatrical	
Variable Effects Engine	Yes	
Effects Parameters	Intensity Effects	

	Studio Force V 48	Studio Force V 72
Hot Lumen Output	White 16,900 hot lumens @ 4,200K	White 25,400 hot lumens @ 4,200K
Optics	Specialised close focus lens	
Beam Angle	~23°	
Beam Angle With Optional Cyc Optic	80 x 30° (approx.)	
Beam Angle With Optional Cyc Optic	60° (approx.)	
Beam Distribution	Asymmetrical direct illumina	tion
CCT	3,000K - 6,100K (+/- 200K)	
Colour Gamut	Performance enhanced	
CRI	≥80	
Lamp Life	L70 at 50,000 hours	

# **Accessories**

CHCFCL48	Cyc Lens For Force 48
CHCFBL48	Border Light Lens For Force 48
CHCFHS48	Half Snoot For Force 48

CHCFCL72	Cyc Lens For Force 72
CHCFBL72	Border Light Lens For Force 72
CHCFHS72	Half Snoot For Force 72

### **Studio Force D Range**

All three Studio Force V models are also available as Studio Force D 6,100K CCT daylight white versions.

For the latest news and information on the Chroma-Q range, visit www.chroma-q.com