

# IES Photometric Report 2inspire 300

Chroma-Q\_2inspire\_300\_Narrow\_2400K.IES



Generated: 5/4/2026 1:39:05 PM

Generated: 5/4/2026 1:39:05 PM

Fixture Information


Manufacturer	Chroma-Q	Max Candela	5317.9 cd
Luminaire	LED Projector Luminaire at 2400K setting	Est. Total Lumens	2170 lm
Lamp	LEDs	Beam Angle (50%)	25.5°
Format	IESNA (unknown version)	Field Angle (10%)	62.8°
Wattage	56.0 W	Phot. Type	Type C (Vertical)
Lumens/Lamp	Absolute	Units	Feet
Num Lamps	1	W x L x H	-0.354 x -0.354 x 0.000
Ballast Factor	1.000		


Photometric Data


V Angles	73 (0° – 180°)
H Angles	17 (0° – 360°)

IES Keywords

[TEST]	P179C
[TESTLAB]	Lumentra
[ISSUEDATE]	Nov 28, 2023
[MANUFAC]	Chroma-Q
[LUMCAT]	2inspire-POE-300 (2400K)
[LUMINAIRE]	LED Projector Luminaire at 2400K setting
[LAMP]	LEDs
[BALLAST]	DC
[BALLASTCAT]	
[_VOLTAGE]	52.74
[_CURRENT]	1.078
[_WATTAGE]	56.7
[_PF]	1.0
[_THD]	0.0
[_LUMENS]	2185
[_EFFICACY]	39.02
[_STABILIZATION TIME]	80









Settings


Distance unit	Meters (m)
Light unit	Lux (lx)
Spread mode	Fixture count
C-Plane	All C-Planes
Output Height	1.6 m
Floor X	5.0 m
Floor Y	5.0 m
Fixture grid	1 x 1 (1)
Wall dist X	0.30 m
Wall dist Y	0.30 m

Results

Peak	353.3 lx
Average	47.3 lx
Min	1.9 lx
Result grid	6 x 6 @ 1.0 m



Beam Intensity



\* at beam centre