

Specification Sheet - Version: 1.5
Chroma-Q™ Magic Box™
EtherSwitch 7™ (1 Gigabit)
Part No: CHES07

DESCRIPTION

The unit shall provide a heavy duty, high speed unmanaged network switch that supports simultaneous computer connections.

The unit shall be equipped with seven shielded EtherCon ports (RJ45) providing 10 / 100 / 1000 Mbps bandwidth in full-duplex mode.

The unit shall enable the concurrent use of various multimedia devices within a network without traffic restrictions.

The unit shall be designed for customised front of house racks.

The unit shall utilise the unique Magic Box interlocking enclosure to facilitate rack mounting when used in single units or pairs and easy truss mounting via captive nut insert.

FEATURES

- Two shielded EtherCon ports (RJ45) at the front panel.
- Five shielded EtherCon ports (RJ45) at the rear panel.
- Easy to see status LED for each port.
- Designed for customised front of house racks.
- Unique Magic Box interlocking enclosure facilitates easy rack mounting when used in single units or pairs and easy truss mounting via captive nut insert.
- Rack mounting brackets are available in single and dual unit versions to enable customisation of equipment racks or installations.
- Upgradable to EtherSwitch 7F (Fibre).

ORDERING INFORMATION

CHES07: Chroma-Q Magic Box EtherSwitch 7

ACCESSORIES

CHMBEAR: Chroma-Q pair of Magic Box rack ears

CHMBEAR-1: Chroma-Q pair of Magic Box extended rack ears

CHESFU: Chroma-Q EtherSwitch Fibre Upgrade

OVERALL SPECIFICATIONS

Net Weight:

Shipping Dimensions:

Net Dimensions: Width: 220mm / 8.6"

Height: 88mm / 3.5" Depth: 280mm / 11" 3.5kg / 7.8lbs Width: 250mm / 9.8"

Height: 125mm / 4.9" Depth: 300mm / 11.8"

Shipping Weight: 4kg / 9lbs

Power: 100-240V AC, 50-60Hz, 0.4A

Power Connector: IEC chassis male

Ethernet Switch Type: Intelligent store & forward

Ethernet Protocols: All IEEE 802.3

RJ45 / EtherCon Port: Shielded 10BaseT / 100BaseTX /

1000BaseT

RJ45 / EtherCon: Auto-negotiation
RJ45 / EtherCon MDI / MDIX: Auto-crossover
RJ45 / EtherCon TD & RD Polarity: Auto-polarity
MAC Addresses Supported: 8192
VLAN Supported: 4096
Jumbo Frame Support: Up to 9.6K
Buffer Memory: 144 Kbytes

Memory Bandwidth: 16 Gbps for full wire speed on all ports

Forwarding Rate: 10 Mbps: 14,880pps

100 Mbps: 14,880pps 148,81pps 1000 Mbps: 1488,1pps 1488,1pps 1488,1pps Link and activity LED

Power: Power LED Colour: Power LED

