



**Chroma-Q™**  
BRILLIANT SOLUTIONS

**Specification Sheet - Version: 1.0**  
**Chroma-Q™ Color Force Compact™**  
**15 Way Power Supply**  
**Part No: CHCFCPSU15**

**DESCRIPTION**

The power supply shall be designed for mounting in a 19" rack.  
The unit shall be 4U (units) high.  
The power supply shall feature a large backlit LCD display.  
The power supply shall feature built-in programming features.  
The power supply shall work as a stand-alone unit.  
The power supply shall come with 23 pre-programmed looks and store up to 31 custom looks on board.  
Unit can be fitted with a W-DMX Upgrade Pack \*at extra cost\*

**FEATURES**

- Controls up to 15 Force Compact Fixture via 3 x 4 Pin Outlets with a maximum of 5 units per line
- 23 Pre-programmed looks
- Stores up to 31 user programmed looks
- 18 Control modes
- Can be mounted in a standard 19" rack
- Backlit LCD display
- Optional Wireless DMX (W-DMX) Upgrade Card Available
- Master slave operation in stand alone mode
- Can be use as a wireless repeater

**ORDERING INFORMATION**

CHCFCPSU15: Chroma-Q Color Force Compact 15 Way Power Supply

**OVERALL SPECIFICATIONS**

Net dimensions:	Width (A): 412mm / 16.9" Height (B): 133mm / 5.2" Depth (C): 268mm / 10.5"
Net weight:	9.5kg / 21lbs
Shipping dimensions:	Width: 508mm / 20" Height: 203mm / 8" Depth: 330mm / 13"
Shipping weight:	11.3kg / 25lb
Power:	100-120V~, 10A; 200-240V~, 5A; 50-60Hz
Power input connector:	IEC
Power & data output connector:	XLR 4-pin
Data input connector:	XLR 5-pin
Control protocol:	ANSI E1.11 DMX-512A / Wireless Option
Power connector:	IEC
Colour:	Black
IP rating:	IP20
Approvals:	CSA C22. No. 166-M1983; R2008 CAN/ CSA-C22.2 No. 60950-1-07 UL 60950-1:2007, EN 60950-1/A1:2010
Operating temperature:	0°C - 40°C

