

# IES Photometric Report 2inspire 100

Chroma-Q\_2inspire\_100\_Medium\_5600K.IES



Generated: 5/4/2026 2:38:54 PM

Generated: 5/4/2026 2:38:54 PM

Fixture Information

Manufacturer	Chroma-Q	Max Candela	1471.1 cd
Luminaire	LED Projector Luminaire at 5600K setting	Est. Total Lumens	756 lm
Lamp	LEDs	Beam Angle (50%)	33.1°
Format	IESNA:LM-63-2002	Field Angle (10%)	71.2°
Wattage	19.5 W	Phot. Type	Type C (Vertical)
Lumens/Lamp	Absolute	Units	Feet
Num Lamps	1	W x L x H	-0.208 x -0.208 x 0.000
Ballast Factor	1.000		


Photometric Data


V Angles	91 (0° – 90°)
H Angles	145 (0° – 360°)


IES Keywords

[TEST]	EV-2002
[TESTLAB]	Spectrum mfg
[ISSUEDATE]	2024-01-24
[MANUFAC]	Chroma-Q
[LUMCAT]	2inspire-POE-100 Medium (5600K)
[LUMINAIRE]	LED Projector Luminaire at 5600K setting
[LAMP]	LEDs
[BALLAST]	DC
[BALLASTCAT]	
[_VOLTAGE]	53.89
[_CURRENT]	0.363
[_WATTAGE]	19.5
[_PF]	1.0
[_THD]	0.0
[_LUMENS]	756.5
[_EFFICACY]	49.4
[_STABILIZATION TIME]	70

Polar Intensity Diagram (view max 1595 cd)








Settings


Distance unit	Meters (m)
Light unit	Lux (lx)
Spread mode	Fixture count
C-Plane	All C-Planes
Output Height	1.6 m
Floor X	5.0 m
Floor Y	5.0 m
Fixture grid	1 x 1 (1)
Wall dist X	0.30 m
Wall dist Y	0.30 m

Results


Peak	123.4 lx
Average	17.1 lx
Min	0.8 lx
Result grid	6 x 6 @ 1.0 m



Iso-Illuminance



Beam Intensity



\* at beam centre