

# IES Photometric Report 2inspire 300

Chroma-Q\_2inspire\_300\_Extra\_Wide\_4800K\_CeilingMount.IES



Generated: 5/4/2026 1:39:02 PM

Generated: 5/4/2026 1:39:02 PM

Fixture Information


Manufacturer	Chroma-Q	Max Candela	1442.9 cd
Luminaire	LED Projector Luminaire at 6500K setting	Est. Total Lumens	1756 lm
Lamp	LEDs	Beam Angle (50%)	55.7°
Format	IESNA:LM-63-2002	Field Angle (10%)	130.6°
Wattage	53.9 W	Phot. Type	Type C (Vertical)
Lumens/Lamp	1757 lm	Units	Meters
Num Lamps	1	W x L x H	-0.120 x -0.120 x 0.000
Ballast Factor	1.000		


Photometric Data


V Angles	181 (0° – 180°)
H Angles	25 (0° – 360°)

IES Keywords

[TEST]	EV-2002
[TESTLAB]	Spectrum mfg
[TESTDATE]	2025-4-29
[MANUFAC]	Chroma-Q
[LUMCAT]	2inspire-POE-300_Extra_Wide_CeilingMount(6500K)
[LUMINAIRE]	LED Projector Luminaire at 6500K setting
[LAMP]	LEDs
[BALLAST]	DC
[BALLASTCAT]	
[_VOLTAGE]	76.8
[_CURRENT]	0.7
[_WATTAGE]	53.8
[_PF]	0.62
[_THD]	0.0
[_LUMENS]	1756
[_EFFICACY]	32.6
[_STABILIZATION TIME]	70









Settings


Distance unit	Meters (m)
Light unit	Lux (lx)
Spread mode	Fixture count
C-Plane	All C-Planes
Output Height	1.6 m
Floor X	5.0 m
Floor Y	5.0 m
Fixture grid	1 x 1 (1)
Wall dist X	0.30 m
Wall dist Y	0.30 m

Results

Peak	264.7 lx
Average	45.5 lx
Min	2.6 lx
Result grid	6 x 6 @ 1.0 m



Beam Intensity



\* at beam centre